

SPECIFICATIONS

| | |
|--|--|
| STYLE NAME: INNOVIOUS HUES | APPROX. WEIGHT PER CARTON: 46.34 LBS. |
| LOCKING SYSTEM: i4F Standard | CARTON SIZE: 7.60"W X 48.79" L X 2.56"H |
| FINISH: Wood Emboss | CARTONS PER PALLET: 55 |
| BEVEL: MICRO BEVEL | SQUARE FEET PER PALLET: 1541.65 SQ. FT. |
| NOMINAL PRODUCT THICKNESS: 5 MM TOTAL (4 MM + 1 MM PAD) | APPROX. WEIGHT PER PALLET: 2,614.88 LBS. |
| NOMINAL PLANK SIZE: 7.00" W X 48.00"L x 0.20" H | PALLETS PER 40 FT. CONTAINER: 21 |
| UNIQUE PLANKS PER SKU: 5 | SQUARE FEET PER 40 FT. CONTAINER: 3,2374.02 SQ. FT. |
| PLANKS PER CARTON: 12 | APPROX. WEIGHT PER 40 FT. CONTAINER: 110,230 LBS. |
| SQUARE FEET PER CARTON: 28.03 SQ. FT. | COUNTRY OF ORIGIN: MANUFACTURED IN VIETNAM |

PERFORMANCE

| | |
|--|--|
| FLOOR SCORE CERTIFIED | ASTM C1028 SCOF: DRY 0.70, WET 0.61 |
| ORTHO PHTHALATE FREE | ASTM F970 STATIC LOAD: PASSES ≤ 250 PSI |
| ASTM E648 CRITICAL RADIANT FLUX: CLASS 1 | ASTM F137 FLEXIBILITY: PASSES 115 MM MANDREL |
| ASTM E662 SMOKE DENSITY: UNDER 450 | ASTM F925 CHEMICAL RESISTANCE: PASSES |
| ASTM F1515 LIGHT STABILITY: < 8.0 DELTA E - PASSES | ASTM F1514 HEAT STABILITY DELTA E < 8.0: PASSES |
| ASTM F2199 DIMENSIONAL STABILITY HEAT: PASSES | ASTM D4060 ABRASION RESISTANCE: 38,000 CYCLES |
| AATCC 134 (STEP) ELECTROSTATIC: 1.5 K.V. OR LOWER | ASTM D2047 COEFFICIENT OF FRICTION: DRY 0.90 |

INSTALLATION

| | |
|---|--|
| END USE: RESIDENTIAL, LIGHT COMMERCIAL | SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST |
| INSTALLATION METHOD: FLOAT | RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F |

DESIGN

PART NUMBER

EAN / UPC NUMBER

| DESIGN | PART NUMBER | EAN / UPC NUMBER |
|----------------------|-------------|------------------|
| HARBOR HICKORY 290L | 60002057 | 190670034372 |
| HONEY HICKORY 221L | 60002058 | 190670034389 |
| JUNIPER HICKORY 626D | 60002059 | 190670034396 |
| CRYSTAL OAK 120L | 60002060 | 190670034402 |
| APRICOT OAK 462D | 60002061 | 190670034419 |
| WILLOW OAK 919M | 60002062 | 190670034426 |
| MINDI OAK 126M | 60002063 | 190670034433 |
| FAWN OAK 692M | 60002064 | 190670034440 |

WARRANTIES

LIFETIME RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 72 HR MOISTURE WARRANTY

10 YEAR LIGHT COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL MOISTURE WARRANTY

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER SPECIALLY FORMULATED FOR USE WITH LAMINATE AND A MICROFIBER MOP.