

**SPECIFICATIONS**

STYLE NAME: <b>OTERRA™</b>	APPROX. WEIGHT PER CARTON: <b>30.04 LBS.</b>
ABRASION CLASS: <b>AC4   CLASS 32</b>	CARTON SIZE: <b>7.91"W X 51.18" L X 2.60"H</b>
LOCKING SYSTEM: <b>ANGLE TAP</b>	CARTONS PER PALLET: <b>68</b>
FINISH: <b>EIR (EMBOSS IN REGISTER)</b>	SQUARE FEET PER PALLET: <b>903.04 SQ. FT.</b>
BEVEL: <b>4 SIDED PAINTED MICRO BEVEL W/ WATER REPELLANT COATING</b>	APPROX. WEIGHT PER PALLET: <b>2,080.72 LBS.</b>
NOMINAL PRODUCT THICKNESS: <b>14MM TOTAL (12MM + 2MM PAD)</b>	PALLETS PER 40 FT. CONTAINER: <b>21</b>
NOMINAL PLANK SIZE: <b>8.03" W X 47.64"L x 0.55" H</b>	SQUARE FEET PER 40 FT. CONTAINER: <b>18,963.84 SQ. FT.</b>
UNIQUE PLANKS PER SKU: <b>7</b>	APPROX. WEIGHT PER 40 FT. CONTAINER: <b>43,695.12 LBS.</b>
PLANKS PER CARTON: <b>5</b>	COUNTRY OF ORIGIN: <b>MANUFACTURED IN USA WITH GLOBAL COMPONENTS</b>
SQUARE FEET PER CARTON: <b>13.28 SQ. FT.</b>	

**PERFORMANCE**

CARB PHASE II: <b>TSCA Title VI Compliant</b>	NALFA 3.9 CHAIR RESISTANCE: <b>CLASS 4</b>
ASTM E648 CRITICAL RADIANT FLUX: <b>CLASS 2</b>	NALFA 3.1 STATIC LOAD: <b>CLASS 3</b>
ASTM E662 SMOKE DENSITY: <b>UNDER 450</b>	NALFA 3.5 LARGE BALL IMPACT RESISTANCE: <b>CLASS 3</b>
NALFA 3.3 XENON LIGHT RESISTANCE: <b>CLASS 3</b>	NALFA 3.6 SMALL BALL DART IMPACT: <b>CLASS 2</b>
NALFA 3.4 CLEANABILITY – STAIN RESISTANCE: <b>CLASS 3</b>	AATCC 134 (STEP) ELECTROSTATIC: <b>1.9 K.V.</b>
NALFA 3.7 WEAR RESISTANCE: <b>CLASS 3</b>	NALFA 3.2 THICKNESS SWELL: <b>CLASS 3</b>
NALFA 3.10 SURFACE BOND: <b>CLASS 3</b>	NALFA 3.2 THICKNESS SWELL: <b>CLASS 3</b>
NALFA 3.8 DIMENSIONAL TOLERANCE: <b>CLASS 4</b>	

**INSTALLATION**

END USE: <b>RESIDENTIAL, COMMERCIAL</b>	RADIANT FLOOR HEAT COMPATIBLE: <b>FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F</b>
INSTALLATION METHOD: <b>FLOAT</b>	INSTALLATION SUNDRIES AS REQUIRED: <b>6 MM POLYETHYLENE SHEETING</b>
SUITABLE GRADE LEVEL: <b>ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST</b>	

**DESIGN**

**PART NUMBER**

**EAN / UPC NUMBER**

DESIGN	PART NUMBER	EAN / UPC NUMBER
STARGAZER OAK 994E	62002430	190670032576
RIVERSTONE OAK 904D	62002431	190670032583
HIGHLAND OAK 626D	62002432	190670032590
PRAIRIE OAK 624M	62002433	190670032606
RIVIERA OAK 169M	62002434	190670032613
CHILEAN OAK 946M	62002435	190670032620
URBAN OAK 919M	62002436	190670032637
NORDIC ASH 296L	62002437	190670032644
ICELANDIC BEECH 021L	62002438	190670032651
DOVER OAK 009S	62002439	190670032668

**WARRANTIES**

LIMITED LIFETIME RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 72 HR MOISTURE WARRANTY

15 YEAR COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL MOISTURE WARRANTY

**CARE & MAINTENANCE**

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER SPECIALLY FORMULATED FOR USE WITH LAMINATE AND A MICROFIBER MOP.